

Single Stanchion

Part #: 15225

Compliant with all OSHA 1910 and OSHA 1926 Subpart M regulations.

Custom configurations not available. Not repairable.
Contact customer service for details.

Single Stanchions are suitable for the following application:



Fall Prevention: When used with compatible warning line, Single Stanchions may be used in Fall Prevention applications ONLY. Fall Prevention Systems are placed around the leading edges of any and all fall hazards to prevent a worker from going over an edge, and may be used in substitute of Fall Protection or safety netting systems. Installation requirements for Fall Prevention Systems set forth in product instruction manual MUST be adhered to. Personal Fall Arrest, Work Positioning, Climbing, Rescue, and any other systems must NEVER be connected to Fall Prevention Systems.



WARNING

Use of equipment in unintended applications may result in serious injury or death. NEVER make any connections to any part of Single Stanchion warning line systems. NEVER lean or climb on Single Stanchion warning line systems.

Materials: galvanized steel.

Set-up: 1) twist open legs; 2) fold up stem; 3) lock into place with provided locking pin.

Maximum spacing between Single Stanchions is 50'.

Single Stanchion systems must be placed MINIMUM 6' from all leading edges of fall hazards, and 10' from leading edges perpendicular to the direction of any mechanical equipment.

Warning Line MUST be between 34" - 39" above working surface.

Recommended for use in combination with Warning Line (part #: 15231).

User must inspect prior to EACH use. Competent Person must complete formal inspection every 6 months, and record inspection on equipment inspection label.

UPC-A Code: 672421152257.

GUARDIAN
FALL PROTECTION

