| | A | В | С | D | E | | F | |
|---|---|----------------------------|---------------|---|---|--------------------------|--|------------------------------|
| 1 | 8 | 8 POINT MEDIUM 6 INC | H CUTTING WIE | | | | | |
| 2 | | | | | | | | |
| | | | | | | | | |
| 3 | | | | | CATALOG NUMBER | QUANTITY | | CRIPTION |
| | | | | | TT8-1856-6P | 57 | CUTTER/TUNG | Л |
| 4 | | | ///// | | WA-1638-3 NOTE: THERE C. MUST BE A CLEA | | | NUMBER |
| 5 | | | | | | | | |
| | | | | | | NEXT ASSY | THIS DRAWING AND THE PARATION CORPORATION APPROVAL REF DWG | APPROVED B |
| 6 | NOTE: 1. PART TO BE FREE OF S SPATTER. | SHARP EDGES, BURRS, SLAG A | ND WELD | | | ANGL 1 PL [2 PL [| ERANCE ES ±.500° ES ES ±.500° ±.500° ±.500° ±.500° ±.500° ±.500° ±.500° ±.500° ±.500° ±.500° ±.500° ±.500° ±.500° ±.500° | BLA NA DRWN /30/06 SHT 1 |
| • | A | В | C | D | E | | F | |

