Shot Blasting Systems

WALK-BEHIND AND SELF-PROPELLED

Blastrac 2-30D Super

The Blastrac 2-30D Super is a powerhouse machine designed for the big jobs that require high productivity. The drive system with integrated brake is designed for ramps and inclines, making the 2-30D ideal for parking decks. A high-speed travel switch on the 2-30D helps ensure uniform surface preparation by allowing for quick repositioning after each pass, without resetting the travel speed.

Use this Blastrac Super system for industrial plant and warehouse floors, parking garages, ship decks, highway or bridge work, airport runways and other large jobs.



Blastrac 2-30D Super

SPECIFICATIONS:

Blasting Width: 30 in. (750mm)

Travel Speed: Up to 92 ft/min. (28m/min)

Prod. Capacity†: Up to 9,000 sq.ft/hr

Blast Motor: 15/20 hp, 2 motors

Amperage: 59.8A Voltage: 460V, 3ø, 60 Hz Dust Collector: 8-54DC or 9-55DC Dimensions: L 75 in. x W 39 in. x H 48 in. Weight: Net 1,575 lb. (714kg)



- 30 inch cleaning path
- Recommended for light to medium removal
- Excellent for warehouse floors or thin mil coating applications
- High-speed travel switch helps ensure uniform profiling by allowing for quick repositioning for successive passes, without resetting travel speed
- Base elevates the machine for easier transport
- Prepares up to 9,000 sq. ft/hr



Production rates achieved will be affected by variables specific to each job site. These figures are not guarantees of performance. For proper operation, the shot blasting unit must be used in conjunction with an appropriate dust collection device.

Always wear appropriate eye, ear and respirator protection for the application, as specified by OSHA regulations and your employer. Never operate or maintain equipment before reading and understanding the instructions for operation and maintenance. Obey all safety signs and instructions while operating or maintaining equipment.

