



CPM-8 SCARIFIER

Equipment Development Co., Inc. sales@edcoinc.com • 800.638.3326 • edcoinc.com


8" WALK BEHIND SCARIFIER

MODEL #	PART #	POWER	HORSE POWER	PHASE	AMPS	*RPM's	BELTS	LENGTH	WIDTH	HEIGHT	WEIGHT
CPM-8-5	79500	Electric	5 HP, 230 V	Single	19.8	2160	Std "V" Belts	35"	20"	39"	220 lbs
CPM-8-5	79400	Electric	5 HP, 230/460 V	Three	12/6	2130	Std "V" Belts	35"	20"	39"	220 lbs
CPM-8-9H	79300	Gasoline	*9 HP	N/A	N/A	2150	Cgd "V" Belts	35"	20"	39"	190 lbs

PRODUCTION RATE: 8" Working Width will scarify approximately 350-500 sq ft per hour at 1/8" Depth Per Pass • Removes traffic lines at 800-1000 lineal feet per hour

PRODUCT NOTES: Optional edger attachment allows the CPM-8 to get within 1/4" of any vertical surface

IDEAL FOR: Sidewalk trip hazard repair • Concrete coatings removal • Floor cleaning and or preparation • Traffic line and markings removal • Creating non-slip surfaces




Scarifier accessories



Edger Assembly Part # 65027 / Edger Drum Part # C66040



MANY CUTTER DRUM SET-UPS INCLUDING DIAMOND BLADE GROOVING ARE AVAILABLE TO ACHIEVE VARIOUS SURFACE PROFILES



* RPM's are based on the machine's accessory speed. * NET HORSEPOWER STATEMENT - *As rated by the engine manufacturer. The power rating of the engine indicated in this document is the net power output tested on a production engine for the engine model and measured in accordance with SAE J1349 at 3600 rpm. Mass production engines may vary from this value. Actual power output for the engine installed in the final machine will vary depending on numerous factors, including the opening speed of the engine in application, environmental conditions, maintenance, and other variables.