## RE. 09/05/19

## HUSQVARNA SURFACE PREP PG 510

The PG 510 is a planetary floor grinder with three grinding discs and a total grinding width of 20 in (515 mm). Performs all types of applications such as concrete grinding, coating removal, concrete repair and polishing. The grinding head on the PG 510 is effectively sealed to keep dust and moisture out. This greatly extends the useful life of the bearings and belts.

The PG 510 is ideal as a rental machine and suitable for both professional and semi-professional work. Quick-release couplings allow the grinding head to be separated from the chassis, which can then be easily folded for transport. The grinder also has a digital hour meter.

| Item No.                             | 967932003                           | 967932004         | 967932005         |
|--------------------------------------|-------------------------------------|-------------------|-------------------|
|                                      |                                     |                   |                   |
|                                      |                                     |                   |                   |
| Technical Specifications             |                                     |                   |                   |
| Power, hp (kW)                       | 3-5.4 (2.2-4.0)                     | 3-5.4 (2.2-4.0)   | 3-5.4 (2.2-4.0)   |
| Voltage, V                           | 440-480                             | 220-240           | 220-240           |
| Plug Type                            | L16-20                              | L15-20            | L6-30             |
| Rated current, amps                  | 7                                   | 15                | 15                |
| UL & CSA approved                    | Yes                                 | Yes               | Yes               |
| Power supply                         | 3-Phase                             | 3-Phase           | 1-Phase           |
| Grinding width, in (mm)              | 20 (515)                            | 20 (515)          | 20 (515)          |
| Grinding disc, in (mm)               | 3 x 9 (230)                         | 3 x 9 (230)       | 3 x 9 (230)       |
| Grinding disc segment capacity       | 18                                  | 18                | 18                |
| Grinding pressure total, lbs (kg)    | 145-176 (66-80)                     | 145-176 (66-80)   | 145-176 (66-80)   |
| Grinding disc speed, rpm             | 669                                 | 669               | 438               |
| Direction of rotation                | Counter Rotation                    | Counter Rotation  | Counter Rotation  |
| Dimensions (L x W x H), in (mm)      | 60 x 21.8 x 37.4 (1525 x 555 x 950) |                   |                   |
| Weight, lbs (kg)                     | 265-293 (120-133)                   | 265-293 (120-133) | 265-293 (120-133) |
| Recommended generator size, kW       | 12                                  | 12                | 12                |
| Recommended dust extractor size, CFM | 285                                 | 285               | 285               |
|                                      |                                     |                   |                   |

## HUSQVARNA CONSTRUCTION PRODUCTS

17400 West 119th Street • Olathe, KS 66061 USA Tel: 800-288-5040 • Fax: 800-825-0028 www.husqvarnacp.com



