

Husqvarna PG 280 SF.

Use the QR-tag
to check out
more about
the PG 280 SF.



The ideal grinder for rental customers who need to grind concrete, mastics, paints, etc. It's small and easy to maneuver, yet strong enough to get the job done.

SURFACE PREPARATION

Applications.

- Perfect for grinding adhesive residue, paint and spackle on medium-sized concrete areas.
- Efficiently grinds due to high rpm levels and a wide range of discs available for various applications.

Benefits.

- The dust guard and vacuum port are designed to create efficient suction of dust and therefore create an almost dustless environment.
- Easy and convenient to use, with ergonomically designed handlebar and low noise levels.
- Large range of diamond tooling available for a wide range of grinding applications.

Accessories.

			P
A	Redi Lock™ diamond disc holder	522677301	\$190.00
B	Rubber damper	510213101	10.75
	Rubber skirt	574272001	48.50
	Resin pad adapter	574653701	115.00

Product specifications.

	PG 280 SF	PG 280 SF	E
Item no.	966987414	966987415	
List price	\$2,799.00	\$3,399.00	

Technical specifications.

Power, hp (kW)	2 (1.5)	3 (2.2)
Voltage, V	115	220-240
Rated current, amps	15	13
Power supply	1-phase	1-phase
Grinding width, in (mm)	11 (280)	11 (280)
Grinding disc, in (mm)	11 (280)	11 (280)
Grinding pressure total, lbs (kg)	55 (25)	55 (25)
Power per grinding disc, hp (kW)	2 (1.5)	3 (2.2)
Grinding disc speed, rpm	1,160	1,440
Dimensions, in (mm) (LxWxH)	47 x 16 x 39 (1,200 x 410 x 1,000)	
Weight, lbs (kg)	176 (80)	176 (80)
Recommended generator size	6 kW	7-1/2 kW



Ergonomically designed handlebar.



Single grinding plate with multiple diamond tool distribution positions.



Redi Lock™ diamond disc holder.



Rubber damper.