

## System Specifications

## IBIX PRO 9 (WET/DRY) ABRASIVE BLAST SYSTEM



PRESSURE ADJUSTABLE:	2.9-123 PSI (0.2-8 BARS)
ABRASIVE RANGE:	30-350 Mesh (0.025-2.5мм)
HOSE LENGTH:	20 гт (6м)
STANDARD NOZZLE:	½" (3мм)
TANK CAPACITY:	9 LITERS (2.4 GALLONS/19.2 LBS.)
USAGE RATE:	0.75-1.5 LBS./FT <sup>2</sup> (AVERAGE)
PERFORMANCE:	35-55 ft²/hr (average)
MINIMUM AIR:	17 CFM
NOISE NUISANCE VALUE:	122.5 DB
SYSTEM HEIGHT (NO HANDLE):	25"
SYSTEM WIDTH:	8" (LEGS DETACHED) 14" (LEGS ATTACHED)
PACKAGING DIMENSIONS (BOX):	14"x17"x31"
MACHINE EMPTY WEIGHT:	39 LBS.
SURFACE CLEANING:	STEEL, ALUMINUM, STAINLESS STEEL, WOOD, GLASS, MARBLE, CONCRETE, MASONRY, STONE, COMPOSITE MATERIALS

Garnet

Calcium Carbonate

## **Approved Abrasive Medias**



Sodium Bicarbonate



Crushed Walnut Shells

IBIX North America www.IBIXUSA.com (727) 322-4611