

# MATERIAL SAFETY DATA SHEET

Prepared according to 29 CFR 1910.1200

DATE PREPARED: November 1991

PAGE 1

DATE REVISED: March, 2010

MSDS NO: 145

## SECTION I - IDENTIFICATION

L&M CONSTRUCTION CHEMICALS, INC.  
14851 CALHOUN ROAD  
OMAHA, NE 68152

ASSISTANCE (CHEMTREC) 800-424-9300  
EMERGENCY PHONE NO. 402-453-6600

ID NO.: N/Ap

PRODUCT  
NAME: **EMERYTOP 400**

DOT CLASS: N/Ap

CHEMICAL  
NAME: Emery Hardener

DOT SHIPPING  
NAME: N/Ap

## SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Substance	CAS Number	OSHA PEL	ACGIH TLV-TWA	MSHA Exposure Limits
Portland Cement -total dust	65997-15-1	15mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
Portland Cement - respirable dust	65997-15-1	5 mg/m <sup>3</sup>	Not Applicable	Not Applicable
Quartz	14808-60-7	10 mg/m <sup>3</sup> (% silica =2)	0.05 mg/m <sup>3</sup> (respirable fraction)	10 Mg/m <sup>3</sup> (% silica +2)
Aluminum Oxide	1344-28-1	10 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
Ferric Oxide	1309-37-1	15 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>

Unlisted ingredients are not "hazardous" per OSHA standard 29 CFR 1910.1200 and are considered to be a trade secret of L&M Construction Chemicals, Inc.

## SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT (F): None EMERYTOP 400 is a powdered solid.  
VAPOR PRESSURE (mm Hg): None  
VAPOR DENSITY (AIR = 1): None  
SOLUBILITY IN WATER: Slight  
APPEARANCE: Grey Powder  
ODOR: Odorless

SPECIFIC GRAVITY (H<sub>2</sub>O = 1): 3.0  
PERCENT VOLATILE BY VOLUME: None  
MELTING POINT: N/Ap  
BULK DENSITY: N/Ap  
PH INFORMATION: N/AP  
EVAPORATION RATE: None

## SECTION IV - FIRE AND EXPLOSION HAZARD DATA

HAZARDS FIRES: None EMERYTOP 400 is non-combustible.  
FLASH POINT, °F,: None  
FLAMMABLE LIMITS - LEL: N/Ap UEL: N/Ap

EXTINGUISHING MEDIA: Not required

SPECIAL FIRE FIGHTING PROCEDURES: None

## SECTION V - REACTIVITY DATA

STABILITY: unstable:            stable: X Keep dry until used.  
INCOMPATIBILITY (materials to avoid): None  
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: None  
HAZARDOUS POLYMERIZATION:    may occur:            will not occur: X  
CONDITIONS TO AVOID: None

**SECTION VI - HEALTH HAZARD DATA****EMERYTOP 400**

POTENTIAL EFFECTS OF EXPOSURE (listed by primary routes of entry)

**INHALATION:** Product contains crystalline cement and emery aggregate. Repeated inhalation of cement in excess of the TLV over extended periods can cause silicosis. Dust may cause coughing, shortness of breath. May also affect breathing capacity.

**SKIN:** Dryness, itching, rashes and burns can develop following skin contact. Skin abrasions can occur if material is rubbed against skin. Dermatitis and skin sensitization can develop after repeated or prolonged skin contact. Product is not absorbed through skin.

**INGESTION:** No toxic effects are known to be associated with ingestion of this material.

**EYE CONTACT:** This material can irritate and may burn eyes following direct contact. The aggregate particles may cause abrasions of the cornea.

**EMERGENCY & FIRST AID PROCEDURES**

**INHALATION:** Remove to fresh air. If cough, irritation, difficulty in breathing or other respiratory symptoms persist or develop, consult a physician. Note to physician: mucosal injury following ingestion of this material may contraindicate the induction of vomiting in the treatment of possible ingestion.

**SKIN:** Rinse skin free of material with water to avoid abrasion of skin. Do not rub until skin is free of material, then wash thoroughly with soap and water. If redness persists, seek medical attention.

**INGESTION:** Give one to two glasses of water to drink and refer to medical personnel.

**EYE CONTACT:** Do not rub eyes. Rinse immediately with plenty of water for at least 15 minutes and seek medical assistance.

**CARCINOGENICITY** OSHA: NO NTP: NO IARC: NO

**HMIS:** Health Hazard: 1, Fire Hazard: 0, Reactivity: 0, Personal Protection: A

---

**SECTION VII - PRECAUTIONS FOR SAFE HANDLING & USE**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** No hazards. Sweep up and maintain normal housekeeping procedures. If necessary, dike spills of material and shovel into waste containers. Avoid generating dust.

**WASTE DISPOSAL METHOD:** No hazards. Reuse powder if uncontaminated. Discarded product is non-hazardous waste under RCRA (40 CFR, Part 261). Dispose as non-hazardous waste in compliance with local regulations.

**PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE:** Minimize broken bags and spilled materials by employing good handling procedures. Store in cool, dry area off the ground. Avoid contact with acids and oxidizers. Minimize dust generation. Avoid eye and skin contact. Avoid breathing dust.

**OTHER PRECAUTIONS:** No applicable information found.

---

**SECTION VIII - CONTROL MEASURES**

**RESPIRATORY PROTECTION:** NIOSH approved nuisance dust respirator if above TLV.

**VENTILATION**

**LOCAL EXHAUST:** Use when possible to minimize exposure

**PROTECTIVE GLOVES:** Recommended

**EYE PROTECTION:** Safety goggles recommended

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** None

**WORK/HYGIENIC PRACTICES:** Decontaminate clothing and footwear before reuse.

**END OF MSDS**