

Intrinsically Safe

Pneumatic Power Contraction Programme Programm









Accessory Package Includes: Vacuum Hose: 2" x 25', Urethane, Static Conductive, Smooth Bore Hose; Wand: 45", Stainless Steel, Single Bend; Crevice Tool: 15", Stainless Steel; Floor Tool: 20", Aluminum Cast w/ Rollers, Rubber Strips; Hose Connector: 2" Male End.

FRV 200 Standard Specifications

- AV-EX2000 Class I Group D, Class II Groups F & G
- **Dual Stainless Steel Venturi**
- Retractable Grounding Reel with Stainless Steel Clamp
- 13 ft² MicroClean BVSC Filter, Manual Shaker System
- 40 ft² HEPA Filter with Minihelic (optional)
- 2" (50mm) Inlet Connection with Bronze Cast Deflector
- Inclusive Sound Suppression, 78 dBA
- 9 Gallon, Foot Lever Actuated Dustpan
- Counterbalanced Base, 3" Heavy Duty Conductive Casters
- Compression Cast Composite Modular Housing
- Carbon Impregnated, Anti-Static 10⁻⁶ Ohms
- Inlet Reducer, 2 3/4"-2" with Button Lock Included
- DEX Accessory Package 202025DEX

Base Price: FRV 200 - \$4,860.00

| ADDER | DESCRIPTION | PRICE |
|-----------|--|------------|
| 35193 | Explosion Proof HEPA Module | \$1,050.00 |
| 24000 | Static Conductive Disposable Dustpan Liner with Lid | \$39.50 |
| 1560OHDEX | Overhead Cleaning Accessory Kit | \$425.00 |
| L-EX | Extended Caster Frame Assembly w/ Antistatic Casters | \$825.00 |