







Bagger : Standard Specifications

- Powerful 110 Volt, Single Phase, 60 Hz, 3 motor
- 288 CFM and 75 H2O" •
- 13 ft² MicroClean Primary Filter 99% Efficient @ 0.5 Microns •
- Mechanical Filter Cleaning Mechanism for Dustless Cleaning ٠
- HEPA 2.0 Secondary Filter 99.97% Efficient @ 0.3 Microns
- 2 3/4" Inlet Connection with Aluminum Cast Deflector •
- Bagged Collection System for Dustless Emptying •
- 3" Heavy Duty Casters in Front, 10" Rough Terrain Wheels on Back •
- Compression Cast "Bulletproof" Composite Modular Housing
- Advanced "Rapid Cool" Heat Displacement •
- Includes 3 Year Pro Series Extended Warranty

Red Line Pro Series Industrial Vacuums are specifically designed to meet and exceed the OSHA Silica **Dust Compliance Standards.**



OSHA Compliancy Table

Up to 7" handgrinders, tuck pointers and handheld crack chasers	8" scarifiers
Up to 8" handheld power saws for fiber board	8" shotblasters
Dowel drilling rigs	Joint cleanout saws
Up to 28" walk behind floor grinders	*Great vacuum for medium-sized platform surface preparation equipment

