Groove Inlay / Plane / Scarify / Prep



Order Number	Power
SPS10.E7.230.1	7.5 HP/1Ø/230V/35A (50-60 Hz)
SPS10.E7.230.3	7.5 HP/3Ø/208-230V/18A (60 Hz)
SPS10.E7.230.3.50	7.5 HP/3Ø/208-230V/18A (50 Hz)
SPS10.E7.380.3	7.5 HP/3Ø/380V/7.5A (50-60 Hz)
SPS10.E7.460.3	7.5 HP/3Ø/460V/8.9A (50-60 Hz)
Removal Cut Width	≤ 10" pp (25cm)
Weight	250 lbs (113kg) w/o drum
Dimensions	38" L x 19" W x 44" H (96 cm x 48 cm x 111 cm)
Optional	Gas powerCutter drum assembly

RemoveFaster.com

SPS10[™] Series Performance Benefits:

The SMITH SPS10 is built in the USA for professionals looking to properly prepare asphalt or concrete surfaces to right surface finishes. **OPTIONAL:**

- 20-yr performance history w/ lifetime warranty
- No-bounce, center-weight-over-drum design Cradle-shock to prevent cutter drum loads
- HD, all-steel construction c/w powder coat
- Industrial AC motor c/w overload, starter, stop
- Precision 10-pt micro-depth control setting
- Reversible handle start/stop control lever
- HTD tensioned no-slip drive w/o moving motor Pitch-height front/rear wheel extensions
- · Swing-style anti-vibration height-adj. handle
- · Maintenance-free drive bearings
- Dual vacuum dust-collection ports • All-surround undercarriage dust guard
- · Precise in-line all-steel rear wheel carrier
- · Fast and easy side-loading cutter drum

- Variety of cutter drum assemblies
- Up-Cut EZOFF carriage
- · Ball-mount hitch for driver use
- · High-speed diamond pulley kit
- Front wheel for smoothing surfaces
- Edger cutter drum assembly
- MaxiVac HEPA vacuums
- Water control w/ optional 5-gal water tank
- Motor protection guard with lifting ring
- Maintenance meter
- · Foot lock parking brake system



Specifications and data are subject to change without notice © 2017 SMITH Manufacturing. All rights reserved.