

Leader in Surface Preparation Equipment

BLASTRAC®

SHOT BLASTING | SCARIFYING | SCRAPING | GRINDING | DUST COLLECTION

1-8DEZ

SPECIFICATIONS:

Blasting Width: 9 in.
Travel Speed: Manual
Prod. Capacity: Up to 250 sq.ft./hr.
Motor: 3.35 hp
Voltage: 120V, 1ø, 50 or 60Hz
Amperage: 18A
Power Cord: 50 ft.
Dust Hose Connection: 2 in.
Dimensions: L 45 in. x W 12.5 in. x H 38 in.
Weight: Net 123 lbs

FEATURES & BENEFITS:

- Lightweight unit is easy to handle and transport
- Maneuvers smoothly with front caster-wheel design
- Simple design uses fewer

moving parts, requires less maintenance

- Can blast within 1½" of front wall and edges to within ¾" when side magnet seals are removed
- Heavy-duty design with thicker liners for increased wear ability
- Operates virtually dust-free when connected to BDC-1216



1-8DEC

SPECIFICATIONS:

Blasting Width: 9 in.
Travel Speed: Manual
Prod. Capacity: Up to 350 sq.ft./hr.
Motor: 3 hp
Voltage: 230V, 1ø, 60Hz
Amperage: 11.5A
Power Cord: 50 ft.
Dust Hose Connection: 2 in.
Dimensions: L 47 in. x W 12 in. x H 39 in.
Weight: Net 181 lbs

FEATURES & BENEFITS:

- Lightweight unit is easy to handle and transport
- Maneuvers smoothly with front caster-wheel design

- Simple design uses fewer moving parts, requires less maintenance
- Can blast within 1½" of front wall and edges to within ¾" when side magnet seals are removed
- Operates virtually dust-free when connected to BDC-1216



1-8DPS30

SPECIFICATIONS:

Blasting Width: 8 in.
Travel Speed: Up to 75 ft./min.
Prod. Capacity: Up to 600 sq.ft./hr.
Blast Motor: 4 hp
Voltage: 230V, 1ø, 60Hz
Amperage: 30A
Power Cord: 35 ft.
Dust Hose Connection: 3 in.
Dimensions: L 51 in. x W 16 in. x H 47 in.
Weight: Net 275 lbs

FEATURES & BENEFITS:

- Drive controls on adjustable steering arm-finger-tip control to operate

- Dust port now designed into shot hopper lid
- Great for decorative concrete applications when preparing for overlays and coatings
- Operates virtually dust-free when connected to BDC-1330



1-10DPS75

SPECIFICATIONS:

Blasting Width: 10 in.
Travel Speed: Up to 98 ft./min
Prod. Capacity: Up to 1290 sq.ft./hr. (120m²/hr)
Blast Motor: 10 hp
Voltage: 230V, 3ø, 60Hz
Amperage: 26A
Power Cord: 50 ft.
Dust Hose Connection: 3 in.
Dimensions: L 63 in. x W 17 in. x H 40 in.
Weight: Net 465 lbs

FEATURES & BENEFITS:

- Easily maneuverable, self-propelled machine-forward and reverse

- Excellent for industrial floor prep, road and airport maintenance, asphalt blasting, decontamination, and much more
- Labor and time-saving shot blasting process
- Operates virtually dust-free when connected to the BDC-3140DBP



1-10DSGI

SPECIFICATIONS:

Blasting Width: 10 in.
Travel Speed: Up to 65 ft./min.
Prod. Capacity: Up to 1937 sq.ft./hr.
Blast Motor: 15 hp
Voltage: 460/230V, 3ø, 60Hz
Amperage: 21/39A
Power Cord: 60 ft.
Dust Hose Connection: 5 in.
Dimensions: L 64 in. x W 18 in. x H 43 in.
Weight: Net 794 lbs

FEATURES & BENEFITS:

- Easily maneuverable, self-propelled machine-forward and reverse

- Excellent for industrial floor prep, road and airport maintenance, ship decks, asphalt blasting, decontamination, and much more
- Operates virtually dust-free when connected to 6-54DC



1-15DSGI

SPECIFICATIONS:

Blasting Width: 15 in.
Travel Speed: Up to 82 ft./min.
Prod. Capacity: Up to 2690 sq.ft./hr. (250m²/hr)
Motor: 20 hp
Voltage: 460/230V, 3ø, 60Hz
Amperage: 27/52A
Power Cord: 60 ft.
Dust Hose Connection: 6 in.
Dimensions: L 71 in. x W 22.5 in. x H 47 in.
Weight: Net 1093 lbs

FEATURES & BENEFITS:

- Easily maneuverable, self-propelled machine-forward and reverse
- Quick-lift rear caster assembly for easy transport

- Excellent for industrial floor prep, road and airport maintenance, ship decks, decontamination, and much more
- Operates virtually dust-free when connected to 6-54DC or 8-54DCSGI



2-20DTMKII


SPECIFICATIONS:

Blasting Width: 20 in.
Travel Speed: Up to 108 ft./min.
Prod. Capacity: Up to 4850 sq.ft./hr. (450m²/hr)
Blast Motor: Twin 15 hp
Voltage: 460V, 3ø, 60Hz
Amperage: 44A
Power Cord: 65 ft.
Dust Hose Connection: 6 in.
Dimensions: L 77 in. x W 28 in. x H 55 in.
Weight: Net 1268 lbs

FEATURES & BENEFITS:

- Easily maneuverable, self-propelled machine-forward and reverse

- Quick-lift rear caster assembly for easier transporting
- Excellent for industrial floor prep, road and airport maintenance, ship decks, decontamination, and much more
- Operates virtually dust-free when connected to 8-54DCSGI



05-67000C

SPECIFICATIONS:

Grinding Width: 7 in.
Prod. Capacity: 150/200ft./hr.
Motor: 6600 rpm
Voltage: 120V, 1ø, 60Hz
Amperage: 15A
Power Cord: 6 ft.
Dust Hose Connection: 2 in.
Dimensions: L 19 in. x W 4.5 in. x H 5 in. w/o handle attached
Weight: Net 9 lbs

FEATURES & BENEFITS:

- Fits into smaller spaces, great for edging walls and obstructions
- Safety switch to guard against unintentional start-ups

- Easily accessible and replaceable carbon brushes
- Die-cast aluminum gear housing
- Auxiliary handle easily positions right, left or top of housing
- Operates virtually dust-free when used with a Blastrac shroud and connected to the BDC-1112EU or BDC-1216



BG-250MKII

SPECIFICATIONS:

Cleaning Path: 10 in.
Electric Disc Speed: 1920 rpm
Gas Disc Speed: 2000 rpm
Electric Motor: 5 hp
Gas Motor: 13 hp Honda
Voltage: 230V, 1ø, 60Hz
Electric Power Cord: 50 ft.
Dust Hose Connection: 3 in.
Dimensions: L 51 in. x W 18 in. x H 44 in.
Weight: Net 322 lbs

FEATURES & BENEFITS:

- Closed circuit which is virtually dust free, when connected to BDC-1216 or BDC-1330DBP
- Special drive system for optimum load distribution

- Easy to transport - lifting handles and lifting eye
- Asymmetric dust exhaust with built-in deflector for improved and optimized dust extraction

Available with an Electric or Gas Motor





Leader in Surface Preparation Equipment

BLASTRAC®

SHOT BLASTING | SCARIFYING | SCRAPING | GRINDING | DUST COLLECTION

BMP-335

BMP-335EHY

SPECIFICATIONS:

Cleaning Path: 13.2 in.
Prod. Capacity: Up to 570 sq.ft./hr.
Drum Diameter: 8.5 in.
Drum Speed: 1000 rpm
Drum Motor: 15 hp
Drive Motor: 2 hp
Voltage: 460V, 3ø, 50/60Hz
Dust Hose Connection: 3 in.

BMP-335GHY

SPECIFICATIONS:

Cleaning Path: 13.2 in.
Prod. Capacity: Up to 570 sq.ft./hr.
Drum Diameter: 8.5 in.
Drum Speed: 1000 rpm
Engine: 15 hp Hatz Diesel
Drum Motor: 15 hp hydraulic
Drive Motor: 2 hp hydraulic
Dust Hose Connection: 3 in.



Works with BDC-3140DBP

BMP-4000

SPECIFICATIONS:

Cleaning Path: Milling/15.75 in. Sawing/15 in.
Electric Motor: 460V, 3ø, 60Hz
Gas Motor: 34kW
3 cylinder diesel engine
Working Speed: 0-35 m/min.
Dimensions: L 78 in. x W 150 in. x H 60 in.
Weight: Net 3417 lbs

FEATURES & BENEFITS:

- Only Ride-On milling machine which can also be used as a sawing machine
- Electric control system for safe working conditions
- Can work up to 1.18 inch from edge



- When wheels are folded in, the drive wheel automatically changes direction
- Operates virtually dust-free when connected to a 6-54DCG or 8-54DCSGI

BDC-1112EU

SPECIFICATIONS:

Air Flow: 82.4 cfm @ hose end, 90 in. of water column
Dust Bin Capacity: 5.5 gal
Voltage: 120V, 1ø, 50/60Hz
Amperage: 10.2A
Filter: M class cartridge filters
Cleaning: Electromagnetic pulse filter
Power Cord: 26 ft.
Dust Hose Connection: 1 3/4 in. and 2 1/4 in.
Dimensions: L 15.7 in. x W 22 in. x H 22 in.
Weight: Net 28 lbs

FEATURES & BENEFITS:

- Compact size is easy to maneuver

- Ideal for handheld tools and small grinding machines
- Can be used for dry applications or wet (without filter)
- Made of tough, easy to clean polyester plastic
- Semi-automatic self-cleaning system for longer filter life
- Offers virtually dust-free operation for most handheld grinders/power tools when properly connected



BDC-1216

SPECIFICATIONS:

Static Pressure: Max 80 in H₂O
Air Flow: 184 cfm max
Dust Bin Capacity: 10.5 gal / 100 lbs
Voltage: 120V, 1ø, 60Hz
Amperage: 13A
Power Cord: 28 ft.
Dust Hose Connection: 2 in.
Dimensions: L 25 in. x W 22.5 in. x H 40 in.
Weight: Net 88 lbs

FEATURES & BENEFITS:

- Compact size is easy to maneuver and transport
- Large filtration surface area with 16 sq.ft.
- Quick-release dust bin



- Maintenance friendly design
- Durable resin-reinforced plastic construction
- Dual-motor design
- Offers virtually dust-free operation for most small to medium grinders and polishers
- HEPA filter available

BDC-1330

SPECIFICATIONS:

Static Pressure: Max 85 in H₂O
Air Flow: 290 cfm max
Dust Bin Capacity: 143 lbs
Voltage: 120V, 1ø, 60Hz
Amperage: 15.8A
Voltage: 230V, 1ø, 60Hz
Amperage: 13A
Power Cord: 30 ft.
Dust Hose Connection: 3 in.
Dimensions: L 25 in. x W 28 in. x H 43 in.
Weight: Net 150 lbs

FEATURES & BENEFITS:

- Maintenance friendly design with easily replaceable filters
- Spring-assist shaker mechanism for manual filter cleaning

Available in either 120V or 230V



- Quick release-and-attach dust bin for easy debris disposal
- Tough steel construction for durable long-life use
- Triple independent motor design for up to 4 hp of suction

BDC-1330DBP/LPP

SPECIFICATIONS:

Static Pressure: Max 84.7 in H₂O
Air Flow: 286 cfm max
Dust Bin Capacity: 26.4 gal.
Voltage: 230V, 1ø, 60Hz
Amperage: 19.5A
Power Cord: 30 ft.
Dust Hose Connection: 2 in. and 3 in.
Dimensions: L 38.5 in. x W 23.6 in. x H 70 in.
Weight: Net 280 lbs

FEATURES & BENEFITS:

- Easily replaceable cartridge filters with fully automatic self-cleaning system for prolonged filter life
- Large filtration surface area with 161 sq.ft.

Available in either removable dust bin or Longpack® bagging system



- Maintenance friendly design
- Overload relief valve
- Electrical overload safety

BDC-3140DBP

SPECIFICATIONS:

Static Pressure: Max 90 in H₂O
Air Flow: 300 cfm max
Dust Bin Capacity: 200 lbs
Voltage: 230V, 3ø, 60Hz
Amperage: 15.6A
Power Cord: 30 ft.
Dust Hose Connection: 2 in., 2 1/4 in., and 3 in.
Dimensions: L 53 in. x W 27.5 in. x H 67 in.
Weight: Net 507 lbs

FEATURES & BENEFITS:

- Easily replaceable cartridge filters with fully automatic self-cleaning system for prolonged filter life
- Large filtration surface area with 161 sq.ft.
- Maintenance friendly



- Quick release-and-attach dust bin
- Durable steel construction
- Overload relief valve to protect compressor
- Electrical overload safety
- Virtually dust-free operation

6-54DCGI

SPECIFICATIONS:

Static Pressure: Max 21 in H₂O
Air Flow: 900 cfm max
Dust Bin Capacity: 170 lbs
Voltage: 230V/460V, 3ø, 60Hz
Amperage: 17/9.51A
Power Cord: 50 ft.
Dust Hose Connection: 2 in., 5 in., and 6 in.
Dimensions: L 53 in. x W 28.75 in. x H 52.25 in.
Weight: Net 915 lbs

FEATURES & BENEFITS:

- Six cartridge filter system provides for comfortable, dust-free working

- Auto-pulse cleaning with 11-second pulses prolongs filter life
- Voltage-sensing dual, three phase power panel for dependable use
- Durable steel construction
- Electrical overload safety
- System matched for use with shot blasters, large grinders and more



8-54DCSGI

SPECIFICATIONS:

Static Pressure: Max 21 in H₂O
Air Flow: 1,650 cfm max
Dust Bin Capacity: 420 lbs
Voltage: 460V, 3ø, 60Hz
Amperage: 14.2A
Power Cord: 50 ft.
Dust Hose Connection: 6 in.
Dimensions: L 75 in. x W 42 in. x H 58 in.
Weight: Net 1,235 lbs

FEATURES & BENEFITS:

- New 4 wheel design for more stability
- Eight cartridge filter system provides for comfortable, dust-free working

- Auto-pulse cleaning with 11-second pulses that prolongs filter life
- Durable steel construction
- Cam-lock, high-capacity dust bin
- Electrical overload safety
- Bin features large wheels and handles for ease of transport and debris disposal

