

TES MAINTENANCE LOG

| | MAX HRS | SERVICE | DATE & HOURS | | | | |
|---|------------|------------------------------------|--------------|--|--|--|--|
| Daily Service should be performed before every job on which the TES unit is to be in operation. Required repairs must be completed before the unit is returned to service. | | | | | | | |
| DAILY | | Check Fluid Level – Add Fluid | | | | | |
| DAILY | | Inspect Solution Hoses | | | | | |
| DAILY | | Inspect Propane Hoses | | | | | |
| DAILY | | Rinse Filter Element | | | | | |
| DAILY | | Inspect & Clean Reservoir Filter | | | | | |
| DAILY | | Inspect TEX box heat exchanger | | | | | |
| DAILY | | Inspect TES hoses & Hose Clamps | | | | | |
| | | | | | | | |
| MONTHLY | 100 | Clean & Lubricate Quick Connects | | | | | |
| | | | | | | | |
| 2 MONTHS | 200 | Flush Pressure Relief Safety Valve | | | | | |
| 2 MONTHS | 200 | Replace Filter Element | | | | | |
| | | | | | | | |
| 3 MONTHS | 300 | Check TES Tire Pressure | | | | | |
| | | | | | | | |
| 6 MONTHS | 600 | Clean Spiro-vent Check Valve | | | | | |
| 6 MONTHS | 600 | Tighten TEX Box Hose Clamps | | | | | |
| | | | | | | | |
| 10 MONTHS | 1000 | Filter System Fluid | | | | | |
| Fluid Filtering to be done after the first 300 hours of operation and every 1000 hours thereafter. Evidence of heavy debris levels may indicate that more frequent Fluid Filtering is required. | | | | | | | |
| | | | | | | | |
| ANNUALLY | 1200 | Check Propane Gas Pressure | | | | | |
| ANNUALLY | 1200 | Check Pilot Flame | | | | | |
| ANNUALLY | 1200 | Check Propane System for Leaks | | | | | |
| ANNUALLY | 1200 | Inspect Combustion Chamber | | | | | |
| ANNUALLY | 1200 | Inspect Heat Exchangers | | | | | |
| ANNUALLY | 1200 | Inspect Burner Tubes | | | | | |
| ANNUALLY | 1200 | Inspect Heater Vent System | | | | | |
| ANNUALLY | 1200 | Clean Fluid Reservoir | | | | | |
| ANNUALLY | 1200 | Test TES Fluid | | | | | |
| ANNUALLY | 1200 | Grease Axles & Swivels on wheels | | | | | |
| | | | | | | | |
| BIANNUALLY | 2400 | Replace TES Fluid | | | | | |
| Fluid should be tested annually or every 1000 hours and replaced at that time as required by test results. | | | | | | | |
| | | | | | | | |

For more information on TES maintenance procedures see Section 3 of your TES Operator’s Manual or contact your TES Distributor.

Servicing, inspection and adjustment of the propane heater must be done by trained technicians in accordance with all applicable local and national codes.